

Appliance - Split type air conditioner

Directive 2009/125/EC

Supplier	Carrier
Outdoor unit	38WHS046A1A0TEE
Indoor unit 1	40WHPF046D1A0TEE

Refrigerant

Type	R32
Global Warming Potential	GWP kgCO ₂ eq 675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Sound power level

		Cooling	Heating
Outdoor unit	dB	61	63
Indoor unit 40WHPF046D1A0TEE	dB	58	58

Cooling

Energy efficiency class		A++
Design load	P _{designc} kW	4.6
Seasonal efficiency	SEER	7.80
Seasonal electricity consumption (*)	Q _{ce} kWh/annum	206

Heating

		Average climate	Colder climate	Warmer climate
Energy efficiency class		A++	-	A+++
Design load	P _{designh} kW	4.0	-	3.4
Seasonal efficiency	SCOP	4.60	-	6.10
Seasonal electricity consumption (*)	Q _{he} kWh/annum	1214	-	783
Back up heating capacity	kW	0.690	-	0.000

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.

T _j = -7 °C	P _{dh} kW	3.54	-	-
T _j = +2 °C	P _{dh} kW	2.15	-	2.15
T _j = +7 °C	P _{dh} kW	1.38	-	1.38
T _j = +12 °C	P _{dh} kW	0.97	-	0.97
T _j = bivalent temperature	P _{dh} kW	3.54	-	3.40
T _j = operation limit temperature	P _{dh} kW	2.93	-	2.93

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Contact details

RIELLO Spa
Via Ing. Pilade Riello, 7 - 37045 Legnago (VR), Italy