

Appliance - Split type air conditioner

Directive 2009/125/EC

Supplier	Carrier
Outdoor unit	38WVSH050A1A0TEE
Indoor unit 1	40WVHW050D1A0TEE

Refrigerant

Type	R32
Global Warming Potential	GWP kgCO ₂ eq 675

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Sound power level

		Cooling	Heating
Outdoor unit	dB	63	63
Indoor unit 40WVHW050D1A0TEE	dB	57	57

Cooling

Energy efficiency class		A++
Design load	P _{designc} kW	5.0
Seasonal efficiency	SEER	7.23
Seasonal electricity consumption (*)	Q _{ce} kWh/annum	242

Heating

		Average climate	Colder climate	Warmer climate
Energy efficiency class		A++	-	A+++
Design load	P _{designh} kW	4.3	-	2.3
Seasonal efficiency	SCOP	4.60	-	6.00
Seasonal electricity consumption (*)	Q _{he} kWh/annum	1309	-	540
Back up heating capacity	kW	0.870	-	0.000

Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.

T _j = -7 °C	P _{dh} kW	3.80	-	-
T _j = +2 °C	P _{dh} kW	2.32	-	2.32
T _j = +7 °C	P _{dh} kW	1.49	-	1.49
T _j = +12 °C	P _{dh} kW	1.74	-	1.74
T _j = bivalent temperature	P _{dh} kW	3.80	-	2.32
T _j = operation limit temperature	P _{dh} kW	2.80	-	2.80

(*) Based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located

Contact details

RIELLO Spa
Via Ing. Pilade Riello, 7 - 37045 Legnago (VR), Italy